

www.surelevel.com.au

SUITE LEVEL
HES GROUT

High Strength, High Performance, Dual teparelian Non-Shrink, Closs C Procision Street.

Suitable for:

Frecheson prouding, where high early strength grown is required.

Enclosed experiment base planes.

Heavy duty support beneath machine base planes.

Heavy duty support beneath machine base planes.

Frechet will payels, became and columns.

Anchesing both, bars on a frienge.

Linderprocing.

Principle bearing and cross rads.

Applications surject to continuous.

20Kg

KYOS, Sustaina Make Depart & Operans.

Last Updated: 10/05/2024

Safety Data Sheet

Product Name: HES Grout (High Early Strength Grout)

		Section 1: Ide	ntification of	Product & Sup	plier:	
1.1	Product Name:	Deep Fill (High Early Strength Grout)				
1.2	Product Identification	These products are classified as hazardous according to criteria of Worksafe Australia.				
1.3	Other Names:	UN #:	None	NIOSH:		
		Hazchem:	None	IMDG:		
		GTEPG:	None	CASS No:	None	
		DG Class	None	Poisons Sched:	None	
		Sub Risk:	None	Pack Grp:	None	
		Spec EPG:	None			
1.4	Primary Use			en mixed with water ourable grout for ma		with Sure Level's g, packing and general
1.5	Application	Deep Fill High Early Strength Plus Grout when mixed with water in accordance with SureLevel's directions, gives a free flowing pourable grout for machinery bedding, packing and general construction.				
1.6	Supplier Information	Sure Level Australia Pty Ltd 12 Northgate Drive, Thomastown Vic 3074. Phone: + 61 3 9464 5753 Fax: + 61 3 9464 3630 Email: info@surelevel.com.au Web: www.surelevel.com.au				
1.7	Emergency Contact	13 11 26 (Poisons Information Centre)				
		Section 2	2: Hazards Id	entification:		
2.1	Classification of the substance or mixture	CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA				
	Physical Hazards	Not classified as	a Physical Hazo	ırd		
2.2	GHS Hazard Classification	Skin Irritation HC-2 (H315), Eye Irritation HC-2A (H319), STOT SE HC-3 (H335), STOT RE HC-2 (H373)				

Info@surelevel.com.au



	Health Hazards	Serious Eye Damage / Eye Irritation: Category 1 Carcinogenicity: Category 1 Specific Target Organ Toxicity (Repeated Exposure): Category 1 Skin Corrosion/Irritation: Category 2 Specific Target Organ Toxicity (Single Exposure): Category 3 (Respiratory Irritation) Specific target organ toxicity (single exposure): Category 3 (Respiratory tract irritation)				
	Hazard Statements	Causes skin irritation - H315 Causes serious eye irritation - H319 May cause respiratory irritation - H335 May cause damage to organs through prolonged or repeated exposure - H373				
	Hazard Statements	Causes skin irritation - H315 Causes serious eye irritation - H319 May cause respiratory irritation - H335 May cause damage to organs through prolonged or repeated exposure - H373				
	Precaution Warning Signs					
		understood P260 Do not brea P264 Wash skin tl when using this p P271 Use only out	the until all safet the dust/fume/ horoughly after product. doors or in a we ctive gloves/pro	y precautions ho gas/mist/vapou handling. P270 E ll-ventilated are	Do not eat, drink or smoke	
2.3	Response	P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313: IF exposed or concerned: Get medical advice/ attention. P310: Immediately call a POISON CENTRE or doctor/physician. P362 + P364: Take off contaminated clothing and wash it before reuse.				
2.4	Storage	P403+P233 Store in a well-ventilated place. Keep container tightly closed P405 Store locked up				
2.5	Disposal	P501 Dispose of c	ontents/contair	ner to an approv	red waste disposal plant.	
	Se	ection 3: Materi	al Composi	tion and Ing	redients	
3.1	Ingredients	Namo	CAS	Content	7	
		Name	CAS	Content	_	
		Portland Cement Silica Sand (Quartz)	65997-15-1 14808-60-7	Medium Medium	-	
		Flow Aid, Plasticiser	-	Very Low	-	
		Contents: High >6	80%, Medium 10-	· ·	Very Low <1%	





		Section 4: First Aid Measures
4.1	Eyes	If product comes into contact with eyes, immediately hold eyes open and wash with fresh running water. Ensure irrigation under the eyelids by occasionally lifting upper and lower lids. If pain persists seek medical attention.
4.2	Skin	If product comes into contact with skin, wash affected areas thoroughly with water and soap, if available. In event of irritation, seek medical attention.
4.3	Inhaled	If dust is inhaled, remove to fresh air. If breathing is shallow, ensure clear airway and apply artificial respiration. Seek medical attention.
4.4	Swallowed	Rinse out with plenty of water. If poisoning occurs, contact doctor or Poisons Information Centre. If swallowed do not induce vomiting. Give a glass of water. Material highly irritating and mildly corrosive if swallowed
4.5	Advice to Physician	Treat Symptomatically
4.6	First Aid Facilities	N/A
4.7	Toxicity	N/A
		Section 5: Firefighting Measures
5.1	Suitable Extinguishing Media	(Non-Flammable Material) Use appropriate fire extinguisher for surrounding environment.
5.2	Specific hazards	Non flammable. May evolve toxic gases if strongly heated.
5.3	Advice for firefighters	No fire or explosion hazard exists.
		Section 6: Accidental Release Measures
6.1	PPE	Wear appropriate clothing, gloves, eye protection and facemask to avoid inhalation and contact with skin or eyes
6.2	Environmental precautions	Do not allow this product to be released into storm water drains, creeks or open bodies of water. Only dispose according to lawful regulations.
6.3	Methods For Cleaning up spills	Dry: Vacuum or using brush or soft broom Wet: Use a Cloth to wipe away excess. Make sure product doesn't pass through a drains, Sewers or water passages.
		Section 7: Handling and Storage
7.1	Precautions for Safe Handling	Avoid generating airborne dust during handling and storage. Avoid prolonged contact with skin. Avoid heavy or prolonged dust inhalation (See TWA Section 8). Engineering dust controls should be used ahead of, or in combination with the wearing of appropriate respiratory protection.





7.2	Conditions for safe storage, including any incompatibilities	Store in original packaging, under dry conditions. Keep fine products stored in closed containers. Avoid the generation of airborne dust.				
	Se	ection 8: Exposure C	ontrol / Persono	al Protection		
8.1	Control Parameters	Each of the ingredients	are listed below with	the exposure limits fo	r each.	
			T	WA]
		Material Name	SWA Australia	SWA Proposed	CAS number	
		Crystalline silica (quartz)	0.05 mg/m3	0.05 mg/m3	14808-60-7	
		Portland cement	10 mg/m3	1 mg/m3	65997-15-1	
8.2	Biological Limits	No biological limit value	es have been entered	d for this product.		
8.3	Personal Protective Equipment					
	Eyes/ Face	Wear safety glasses or avoid contact with eyes		when handling materic	al to	
	Hands	Wear PVC, rubber or cor prevent skin contact.	tton gloves when hai	ndling material to		
	Body	Wear long sleeved shirt and full-length trousers				
	Respiratory	Where an inhalation risk exists wear a Class P1 (Particulate) respirator, dependent on a site specific risk assessment.				
8.4	Environmental Exposure Controls	All ventilation systems should be filtered before discharge to atmosphere.				
		Section 9: Physical	and chemical F	Properties		
9.1	Form	Fine grey sand/cement	based powder. No o	dour.		
9.2	Specific Gravity	1.5 Loose				
9.3	Flammability Limited	N/A				
9.4	Form	N/A				
9.5	Boiling Point	N/A				
9.6	Melting Point	N/A				
9.7	Flashpoint	Not Flammable				
9.8	Solubility	Partly Miscible				
9.9	Other Properties:	-				
		Section 10: Sta	bility and Reac	tivity		
10.1	Chemical Stability	This product contains c mixed with water	ement which will und	dergo a hydration reac	tion when	





10.2	Possibility of hazardous reactions	N/A		
10.3	Incompatible Materials	N/A		
10.4	Conditions to Avoid	Extreme temperature, Product is stable under normal temperatures and conditions		
10.5	Reactivity and Stability	Reacts with incompatible materials.		
		Section 11: Toxicological Information		
11.1	Information & Symptoms associated with exposure			
	Acute Toxicity:	N/A		
	Skin corrosion/irritation	Dust is irritating and may cause drying of the skin. Mixed material is moderately irritating to the skin. Constant contact with the skin may cause drying of the skin which may lead to dermatitis and may cause in some cases sensitisation.		
	Serious eye damage/irritation:	The dust is highly irritating and abrasive to the eye. Dust is capable of causing pain and conjunctivitis.		
	Ingestion	Ingestion of this product may irritate the gastric tract causing nausea and vomiting.		
	Repeated Exposure:	Causes damage to organs lungs through prolonged or repeated exposure by inhalation.		
	Inhalation:	Dust is irritating to upper respiratory tract and lungs. Over exposure to respirable dust may cause coughing, wheezing and irritation to the nasal passages.		
	Aspiration Hazard	N/A		
	Swallowed:	Material is irritating and mildly corrosive if swallowed. Ingestion may result in nausea, abdominal irritation, pain and vomiting.		
	Chronic:	Long term exposure to high dust concentrations may cause irritation to lungs and result in breathing disorders, as cement and silica sand is now classified as carcinogenic. Contact with skin, inhalation of dust, vapor ingestion in any form should be avoided. Sensitisation may result in allergic dermatitis responses including rash, itching, swelling of extremities, redness and irritation.		
		Section 12: Ecological Information:		
12.1	Eco toxicity	This product is not expected to be hazardous to the environment		
12.2	Degradability	When products hydrates, it will solidify with time making it non degradable.		
12.3	Bio-accumulative potential	No literature available		
12.4	Mobility in Soil	No literature available		
12.5	Other adverse effects	No literature available		
		Section 13: Disposal Consideration:		
13.1	Disposal	Disposal shall be in accordance with local rules and regulations, in a method to minimize the generation of dust from it and its contact with water. PPE are required for disposal.		





		Section 14: Dispos	sal Consideration:		
14.1	Transport Information	Not classified as dangerous goods and is Safe to transport by sea, land or Air when packed in closed containers. According to: Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code) (7th edition) International Maritime Dangerous Goods Code (IMDG Code) International Air Transport Association (IATA) Dangerous Goods Regulations			
		Section 15: Regule	atory Information:		
15.1	GHS Classification	Hazardous			
15.2	SUSMP	Not Classified as a poisonous material			
		Section 16: Supplem	nentary information		
16.1	Preparation Date	10/05/2024			
16.2	Review & Updates	This SDS will be reviewed periodically every 2 Years and updated accordingly with any regulations.			
		Section 17: Safe Ha	ndling Information		
17.1	Storage & Transport	Multi-ply paper bag with sealed plastic liner or heavy gauge plastic bag or bucket. Check that all containers are clearly labeled and free from leaks.			
17.2	Packaging & Labelling	Packaging and labelling as recommended by Sure Level.			
17.3	Spills & Disposals	Sweep up spills and dispose of in an approved disposal site. Avoid generating dust.			
17.4	Reactivity Data	N/A			
		Section 18: Fire/e	explosion Hazard		
18.1	GHS Classification	Extinguishing Media: Upper Explosion Limit: Lower Explosion Limit: Dust Explosion Limit: May Decompose Explosively: Hazardous Decomposition Products:	Water mist, CO2 , Foam, Dry Powder Not Determined No No No No		

Document Date: February, 2024 (Rev 1.2)

Contact Details

Entity name: SURE LEVEL INTERNATIONAL PTY LTD **Location:** 12 Northgate Dr, Thomastown VIC 3074

Phone: + 61 3 9464 5753

Email: info@surelevel.com.au
website: www.surelevel.com.au