

EXPANDA FOAM Revision Number 2

Revision date 16-Mar-2020 Supersedes Date: 01-Jun-2017

Section 1: Identification: Product identifier and chemical identity

Product identifier

Product Name EXPANDA FOAM

Product Code(s) 30610110

30610110; 30610226

Other means of identification

Proper Shipping Name Aerosols

UN Number UN1950

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Insulation foams

Uses advised against No information available

Details of manufacturer or importer

Supplier

Bostik Australia Pty Ltd 51-71 High Street, Thomastown Victoria

Australia

Tel: 613 9279-9333 Fax: 613 9279-9342

ABN: 79 003 893 838

E-mail address au-bostik-sds@bostik.com

Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

Section 2: Hazard(s) identification

GHS Classification

Based on available information, this material is classified as hazardous according to criteria of Safe Work Australia

aerosols	Category 1 - (H222)
Gases under pressure	Compressed gas - (H229)
Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2A - (H319)
Respiratory sensitization	Category 1 - (H334)
Skin sensitization	Category 1 - (H317)
Carcinogenicity	Category 2 - (H351)
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Specific target organ toxicity (repeated exposure)	Category 2 - (H373)

Australia - EN Page 1 / 12

EXPANDA FOAM
Revision Number 2

·

Revision date 16-Mar-2020

Supersedes Date: 01-Jun-2017

Label elements

Gas cylinder Flame Exclamation mark Health hazard



Signal word

Danger

Hazard statements

- H222 Extremely flammable aerosol
- H229 Pressurized container: May burst if heated
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H335 May cause respiratory irritation
- H351 Suspected of causing cancer
- H373 May cause damage to organs through prolonged or repeated exposure

Precautionary Statements - Prevention

- P201 Obtain special instructions before use
- P202 Do not handle until all safety precautions have been read and understood
- P281 Use personal protective equipment as required
- P271 Use only outdoors or in a well-ventilated area
- P264 Wash face, hands and any exposed skin thoroughly after handling
- P284 In case of inadequate ventilation wear respiratory protection
- P272 Contaminated work clothing should not be allowed out of the workplace
- P280 Wear protective gloves
- P260 Do not breathe dust/fume/gas/mist/vapors/spray
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P251 Pressurized container: Do not pierce or burn, even after use
- P211 Do not spray on an open flame or other ignition source

Precautionary Statements - Response

- P308 + P313 IF exposed or concerned: Get medical advice/attention
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P337 + P313 If eye irritation persists: Get medical advice/attention
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water
- P362 Take off contaminated clothing and wash before reuse
- P333 + P313 If skin irritation or rash occurs: Get medical advice/attention
- P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician

Precautionary Statements - Storage

- P405 Store locked up
- P403 + P233 Store in a well-ventilated place. Keep container tightly closed
- P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
- P410 Protect from sunlight

Precautionary Statements - Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other hazards which do not result in classification

Australia - EN Page 2/12

EXPANDA FOAMRevision date16-Mar-2020Revision Number2Supersedes Date:01-Jun-2017

Persons already sensitized to diisocyanates may develop allergic reactions when using this product

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number S6

Label requirements in accordance with SUSMP

POISON

KEEP OUT OF REACH OF CHILDREN

READ SAFETY DIRECTIONS BEFORE OPENING OR USING

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

<u>Mixture</u>

Chemical name	CAS No.	Weight-%
Isocyanic acid, polymethylenepolyphenylene ester	9016-87-9	30 - 60%
Reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and Phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and Phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester	ECKNOWN	10 - <30
Isobutane	75-28-5	1 - 10%
Propane	74-98-6	1 - 10%
Butane	106-97-8	1 - 10%
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures

Emergency telephone number Poisons Information Center, Australia: 13 11 26

Poisons Information Center, New Zealand: 0800 764 766

FIRST AID

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get

medical advice/attention.

Inhalation Remove to fresh air. May cause allergic respiratory reaction. If breathing has stopped,

give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Get immediate medical

advice/attention.

Eye contactRinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and

persists. Consult an ophthalmologist.

Skin contact In case of contact with liquefied gas, thaw frosted parts with lukewarm water. May cause

an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.

Wash off immediately with soap and plenty of water for at least 15 minutes.

Ingestion May produce an allergic reaction. Do NOT induce vomiting. Never give anything by

mouth to an unconscious person. Get immediate medical advice/attention. Clean mouth

with water. Drink 1 or 2 glasses of water.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the

material(s) involved, take precautions to protect themselves and prevent spread of

Australia - EN Page 3 / 12

Revision Number 2 Supersedes Date: 01-Jun-2017

contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. See section 8 for more information. Avoid breathing vapors or mists.

Revision date 16-Mar-2020

Most important symptoms and effects, both acute and delayed

Symptoms May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/

or wheezing. Itching. Rashes. Hives. Burning sensation. Difficulty in breathing.

Indication of any immediate medical attention and special treatment needed

May cause sensitization in susceptible persons. Treat symptomatically. Note to physicians

Section 5: Firefighting measures

Suitable extinguishing media

EXPANDA FOAM

Suitable extinguishing media Dry chemical. Carbon dioxide (CO2). Water spray.

DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED. Unsuitable extinguishing media

Specific hazards arising from the chemical

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket. Product is or contains a sensitizer. May cause sensitization by inhalation and skin contact.

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

Special protective actions for fire-fighters

Special protective equipment for fire-fighters

gear. Use personal protection equipment.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Use personal protective equipment as required. See Personal precautions

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Contents under pressure. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld

containers. Avoid breathing vapors or mists.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or

spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce

vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches

Australia - EN Page 4 / 12

EXPANDA FOAM
Revision Number 2

evision Number 2 Supersedes Date: 01-Jun-2017

and waterways. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up

Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Revision date 16-Mar-2020

Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Provide extract ventilation to points where emissions occur. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash before reuse.

General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Keep at temperatures between 5 and 25 °C.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

This material is a scheduled poison and must be stored, maintained and used in accordance with the relevant regulations

Section 8: Exposure controls and personal protection

Control parameters

Exposure Limits

Chemical name	Australia
Isocyanic acid, polymethylenepolyphenylene ester 9016-87-9	0.02 mg/m³ TWA 0.07 mg/m³ STEL
Butane	800 ppm TWA
106-97-8	1900 mg/m³ TWA

OEL as published by Safe Work Australia

Australia - EN Page 5/12

EXPANDA FOAM Revision Number 2 **Revision Number** 2 **Revision Number** 2 **Revision Number** 2 **Revision Number** 2

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

Antistatic boots.

Hand protection Impervious gloves. Wear suitable gloves.

Respiratory protectionNo protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical stateAerosolAppearanceFoamColorBeigeOdorCharacteristic

Odor threshold No information available

Property Values Remarks • Method

pH No data available
Melting point / freezing point
Boiling point / boiling range
Flash point
Evaporation rate
No data available
Not applicable, Aerosol .
Not applicable, Aerosol .
No data available

Flammability (solid, gas)

No data available

Flammability Limit in Air

Upper flammability or explosive 16%

limits

 $\ \ \, \text{Lower flammability or explosive} \ \, 3\%$

limits

Vapor pressure 550

Vapor density No data available

Relative density 0.996

Immiscible in water Water solubility Solubility(ies) No data available **Partition coefficient** No data available **Autoignition temperature** No data available **Decomposition temperature** No data available Kinematic viscosity No data available Dynamic viscosity No data available **Explosive properties** No information available **Oxidizing properties** No information available

Other information

Solid content (%) No information available

VOC Content (%) 122 g/L

Density No information available

Section 10: Stability and reactivity

Reactivity

Australia - EN Page 6 / 12

EXPANDA FOAM Revision Number 2 **Revision Number** 2 **Revision Number** 2 **Revision Number** 2

Reactivity No information available.

Chemical stability

Stability Stable under normal conditions.

Explosion Data

Sensitivity to mechanical

Yes.

impact

Sensitivity to static discharge Yes.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks. Excessive heat.

Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products

Hazardous decomposition

products

Nitrogen oxides (NOx). Carbon oxides. Thermal decomposition can lead to release of

irritating and toxic gases and vapors.

Section 11: Toxicological information

Acute Toxicity

Information on likely routes of exposure

Product Information .

Inhalation Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal. Specific test data for the substance or mixture is not available. May cause sensitization in susceptible persons. (based on components). May cause irritation of

respiratory tract. Harmful by inhalation.

Eye contact Irritating to eyes. Causes serious eye irritation.

Skin contact Specific test data for the substance or mixture is not available. Repeated or prolonged

skin contact may cause allergic reactions with susceptible persons. (based on components). May cause sensitization by skin contact. Causes skin irritation.

Ingestion Specific test data for the substance or mixture is not available. May cause additional

affects as listed under "Inhalation". Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhea.

Symptoms Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing,

tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes. Hives. Redness. May cause

redness and tearing of the eyes.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 6,124.00 mg/kg ATEmix (inhalation-dust/mist) 3.20 mg/l

Australia - EN Page 7/12

EXPANDA FOAM Revision Number 2 **Revision Number** 2 **Revision Number** 2 **Revision Number** 2 **Revision Number** 2

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Isocyanic acid, polymethylenepolyphenylene	LD50 > 10000 mg/kg (Rattus)	LD 50 > 9400 mg/kg (Oryctolagus cuniculus)	=1.5 mg/L (Rattus) 4 h
ester			
Reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and Phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and Phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester	LD50 > 500 mg/kg (males); LD50 = 632 mg/kg (females)(Rattus)	LD50 > 2000 mg/kg	-
Isobutane	-	-	=658 mg/L (Rattus) 4 h
Propane	-	-	>800000 ppm (Rattus) 15 min
Butane	-	-	=658 g/m3 (Rattus) 4 h

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	n Classifi	Classification based on data available for ingredients. Causes skin irritation.			
Component Information					
Isocyanic acid, polymethy	ylenepolyphenylene	ester (9016-87-9)			
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit				Mild skin irritant
Acute Dermal					
Irritation/Corrosion					

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization May cause sensitization by inhalation. May cause sensitization by skin contact.

ricepitatery or extil constitution	ii may caace comen	-and of the analysis and the	mentization of crim contacti
Component Information			
Isocyanic acid, polymethylenepoly	yphenylene ester (9016	6-87-9)	
Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig		No sensitization responses
Sensitization			were observed
OECD Test No. 429: Skin	Mouse		sensitizing
Sensitisation: Local Lymph Node			
Assay			

Germ cell mutagenicity No information available.

Carcinogenicity .

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	Australia
Isocyanic acid, polymethylenepolyphenylene ester	Carc. 2
9016-87-9	
Isobutane	Carc. 1A
75-28-5	
Butane	Carc. 1A
106-97-8	
Component Information	
Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)	

Australia - EN Page 8 / 12

EXPANDA FOAM
Revision Number 2

Revision date 16-Mar-2020 Supersedes Date: 01-Jun-2017

Method	Species	Results
OECD Test No. 453: Combined Chronic	Rat	Carcinogenic
Toxicity/Carcinogenicity Studies		

Reproductive toxicity No information available.

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Not applicable.

Section 12: Ecological information

Ecotoxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Isocyanic acid, polymethylenepolypheny lene ester 9016-87-9	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	CL50 (96h) >1000 mg/L (Danio rerio)	-	EC50 (24H) >1000 mg/L Daphnia magna
Reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methyleth yl) phosphate and Phosphoric acid, bis(2-chloro-1-methyleth yl) 2-chloropropyl ester and Phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester ECKNOWN		LC50 (96h) = 56.2 mg/L (Pimephales promelas) Static	-	LC50 (48h) = 131 mg/L Daphnia magna

Persistence and degradability

Persistence and degradability No information available.

Component Information			
Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)			
Method	Exposure time	Value	Results
OECD Test No. 302C: Inherent	28 days	0% biodegradation	Not readily biodegradable
Biodegradability: Modified MITI Test	:	_	
(II)			

Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Reaction mass of tris(2-chloropropyl) phosphate and	2.68
tris(2-chloro-1-methylethyl) phosphate and Phosphoric acid,	
bis(2-chloro-1-methylethyl) 2-chloropropyl ester and	

Australia - EN Page 9 / 12

EXPANDA FOAM Revision Number 2 **Revision Number** 2 **Revision Number** 2 **Revision Number** 2 **Revision Number** 2

Phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester ECKNOWN	
Isobutane 75-28-5	2.88
Propane 74-98-6	2.3
Butane 106-97-8	2.89

Mobility

Mobility in soilNo information available.MobilityNo information available.

Other Adverse Effects

Other adverse effects No information available.

Section 13: Disposal considerations

Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local

regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

Section 14: Transport information

ADG

UN Number UN1950 Proper shipping name Aerosols Hazard Class 2.1

Special Provisions 63, 190, 277, 327, 344, 381

ADG Limited Quantity See SP 277

Description UN1950, Aerosols, 2.1

IATA

UN number UN1950 Transport hazard class(es) 2.1 ERG Code 10L

Special Provisions A145, A167, A802

Limited Quantity (LQ) 30 kg G

Description UN1950, Aerosols, flammable, 2.1

IMDG

UN number UN1950
Transport hazard class(es) 2.1
EmS-No. F-D, S-U
Limited Quantity (LQ) See SP277

Special Provisions 63,190, 277, 327, 344, 381, 959

Marine Pollutant Np

Description UN1950, Aerosols, 2.1

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

Australia - EN Page 10 / 12

EXPANDA FOAM Revision date 16-Mar-2020 **Revision Number** 2 Supersedes Date: 01-Jun-2017

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number S6

Major hazard (accident/incident planning) regulation

Verify that license requirements are met

Threshold quantity (T) Hazardous chemical

Compressed or liquefied gases of Division 2.1 or Subsidiary

Risk 2.1

National pollutant inventory

No substance(s) listed on inventory

Chemical name	National pollutant inventory
Isobutane	20 MW Threshold category 2b total
75-28-5	60000 MWH Threshold category 2b total
	1 tonne/h Threshold category 2a total
	25 tonne/yr Threshold category 1a total
	400 tonne/yr Threshold category 2a total
	2000 tonne/yr Threshold category 2b total
Propane	20 MW Threshold category 2b total
74-98-6	60000 MWH Threshold category 2b total
	1 tonne/h Threshold category 2a total
	25 tonne/yr Threshold category 1a total
	400 tonne/yr Threshold category 2a total
	2000 tonne/yr Threshold category 2b total
Butane	20 MW Threshold category 2b total
106-97-8	60000 MWH Threshold category 2b total
	1 tonne/h Threshold category 2a total
	25 tonne/yr Threshold category 1a total
	400 tonne/yr Threshold category 2a total
	2000 tonne/yr Threshold category 2b total

International Inventories

AICS	Not Listed
NZIoC	Not Listed
ENCS	Not Listed
IECSC	Not Listed
KECL	Not Listed
PICCS	Not Listed

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

ENCS - Japan Existing and New Chemical Substances **IECSC** - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances **PICCS** - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

Australia - EN Page 11/12

EXPANDA FOAM Revision Number 2 **Revision Number** 2 **Revision Number** 2 **Revision Number** 2

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Section 16: Any other relevant information

Prepared By Product Safety & Regulatory Affairs

Revision date 16-Mar-2020

Revision note

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

C Carcinogen

Section 11: TOXICOLOGICAL INFORMATION

LD50 (lethal dose)

Section 12: Ecological information

EC50 (effective concentration)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

Australia - EN Page 12 / 12