



# SAFETY DATA SHEET

ANCHORWELD 6031 PANEL ADHESIVE  
Revision Number 2.03

Revision date 09-Aug-2022  
Supersedes Date: 07-Jul-2022

## Section 1: Identification: Product identifier and chemical identity

### Product identifier

Product Name ANCHORWELD 6031 PANEL ADHESIVE

Product Code(s)  
30608531  
30608531; 30840551

### Other means of identification

Proper Shipping Name Adhesives

UN number or ID number UN1133

Pure substance/mixture Mixture

### Recommended use of the chemical and restrictions on use

Recommended use Adhesive

Uses advised against No information available

### Details of manufacturer or importer

#### Supplier

Bostik Australia Pty Ltd  
51-71 High Street,  
Thomastown Victoria  
Australia  
Tel: 613 9279-9333  
Fax: 613 9279-9342

ABN: 79 003 893 838

E-mail address au-bostik-sds@bostik.com

### Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

## Section 2: Hazard(s) identification

### GHS Classification

Flammable liquids	Category 2 - (H225)
Aspiration hazard	Category 1 - (H304)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Reproductive toxicity	Category 2 - (H361)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Specific target organ toxicity (repeated exposure)	Category 2 - (H373)

### Label elements

# SAFETY DATA SHEET

**ANCHORWELD 6031 PANEL ADHESIVE**  
Revision Number 2.03

Revision date 09-Aug-2022  
Supersedes Date: 07-Jul-2022

Flame  
Exclamation mark  
Health hazard



**Signal word**  
DANGER

## **Hazard statements**

H225 - Highly flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H361d - Suspected of damaging the unborn child  
H373 - May cause damage to organs through prolonged or repeated exposure  
Repeated exposure may cause skin dryness or cracking

## **Precautionary Statements - Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Wear protective gloves/clothing and eye/face protection  
Wash face, hands and any exposed skin thoroughly after handling  
Use only outdoors or in a well-ventilated area  
Do not breathe dust/fume/gas/mist/vapors/spray  
Ground and bond container and receiving equipment  
Use non-sparking tools  
Take action to prevent static discharges  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
Keep container closed  
Keep cool

## **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
IF ON SKIN: Wash with plenty of water and soap  
If skin irritation occurs: Get medical advice/attention  
Take off contaminated clothing and wash it before reuse  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]  
IF INHALED: Remove person to fresh air and keep comfortable for breathing  
Call a doctor if you feel unwell  
IF SWALLOWED: Immediately call a doctor  
Do NOT induce vomiting  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

## **Precautionary Statements - Storage**

Store in well-ventilated place

## **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

## **Other hazards which do not result in classification**

In use, may form flammable/explosive vapor-air mixture.

## **Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)**

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

# SAFETY DATA SHEET

ANCHORWELD 6031 PANEL ADHESIVE  
Revision Number 2.03

Revision date 09-Aug-2022  
Supersedes Date: 07-Jul-2022

Poison Schedule Number 5

## Label requirements in accordance with SUSMP

CAUTION  
KEEP OUT OF REACH OF CHILDREN  
READ SAFETY DIRECTIONS BEFORE OPENING OR USING

## Section 3: Composition and information on ingredients, in accordance with Schedule 8

### Substance

Not applicable

### Mixture

Chemical name	CAS No	Weight-%
Naphtha, petroleum, hydrotreated light, <0.1% Benzene	64742-49-0	30 - 60
Acetone	67-64-1	10 - <30
Toluene	108-88-3	10 - <30
Pentane	109-66-0	0 - <10
Hexane	110-54-3	0 - <10
Zinc oxide	1314-13-2	0 - <10
Rosin	8050-09-7	0 - <10
Non-hazardous ingredients	Proprietary	Balance

## Section 4: First aid measures

**Emergency telephone number** Poisons Information Center, Australia: 13 11 26  
Poisons Information Center, New Zealand: 0800 764 766

### Description of first aid measures

- General advice** Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
- Inhalation** Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical attention. Delayed pulmonary edema may occur.
- Eye contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
- Skin contact** Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.
- Ingestion** Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical attention.
- Self-protection of the first aider** Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing.

# SAFETY DATA SHEET

ANCHORWELD 6031 PANEL ADHESIVE  
Revision Number 2.03

Revision date 09-Aug-2022  
Supersedes Date: 07-Jul-2022

## Most important symptoms and effects, both acute and delayed

**Symptoms** Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

## Indication of any immediate medical attention and special treatment needed

**Note to physicians** Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

## Section 5: Firefighting measures

### Suitable Extinguishing Media

**Suitable extinguishing media** Dry chemical. Carbon dioxide (CO<sub>2</sub>). Water spray. Alcohol resistant foam.

**Unsuitable extinguishing media** No information available.

### Specific hazards arising from the chemical

**Specific hazards arising from the chemical** Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

**Hazardous combustion products** Carbon oxides. Hydrocarbons. Hydrogen chloride.

### Special protective actions for fire-fighters

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

**Hazchem code** •3YE

## Section 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

**Other information** Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Use personal protection recommended in Section 8.

### Environmental precautions

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

### Methods and material for containment and cleaning up

**Methods for containment** Do not scatter spilled material with high pressure water streams. Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam

# SAFETY DATA SHEET

ANCHORWELD 6031 PANEL ADHESIVE  
Revision Number 2.03

Revision date 09-Aug-2022  
Supersedes Date: 07-Jul-2022

may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

**Methods for cleaning up** Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

## Precautions to prevent secondary hazards

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

## **Section 7: Handling and storage, including how the chemical may be safely used**

### Precautions for safe handling

**Advice on safe handling** Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

**Recommended storage temperature** Keep at temperatures between 41 and 77 °F / 5 and 25 °C.

**Incompatible materials** Strong acids. Strong bases. Strong oxidizing agents.

This material is a scheduled poison and must be stored, maintained and used in accordance with the relevant regulations

## **Section 8: Exposure controls and personal protection**

### Control parameters

#### **Exposure Limits**

Chemical name	Australia
Acetone 67-64-1	TWA: 500 ppm TWA: 1185 mg/m <sup>3</sup> STEL: 1000 ppm STEL: 2375 mg/m <sup>3</sup>
Toluene 108-88-3	TWA: 50 ppm TWA: 191 mg/m <sup>3</sup> STEL: 150 ppm

# SAFETY DATA SHEET

ANCHORWELD 6031 PANEL ADHESIVE  
Revision Number 2.03

Revision date 09-Aug-2022  
Supersedes Date: 07-Jul-2022

	STEL: 574 mg/m <sup>3</sup>
Pentane 109-66-0	TWA: 600 ppm TWA: 1770 mg/m <sup>3</sup> STEL: 750 ppm STEL: 2210 mg/m <sup>3</sup>
Hexane 110-54-3	TWA: 20 ppm TWA: 72 mg/m <sup>3</sup>
Zinc oxide 1314-13-2	TWA: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>
Rosin 8050-09-7	TWA: 0.1 mg/m <sup>3</sup>

OEL as published by Safe Work Australia

## Biological occupational exposure limits

### Appropriate engineering controls

**Engineering controls** Showers, eyewash stations, and ventilation systems.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Tight sealing safety goggles.

**Skin and body protection** Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

**Hand protection** Wear suitable gloves. Impervious gloves.

**Respiratory protection** Organic gases and vapors filter conforming to EN 14387.

**Environmental exposure controls** No information available.

## Section 9: Physical and chemical properties

### Information on basic physical and chemical properties

**Physical state** Liquid  
**Appearance** Paste  
**Color** Light yellow  
**Odor** Solvent  
**Odor threshold** No information available

Property	Values	Remarks • Method
<b>pH</b>	No data available	Not applicable Insoluble in water
<b>pH (as aqueous solution)</b>	No data available	
<b>Melting point / freezing point</b>	No data available	
<b>Initial boiling point and boiling range</b>	110 - 111 °C	Toluene
<b>Flash point</b>	> -10 °C	Toluene
<b>Evaporation rate</b>	No data available	
<b>Flammability</b>	Not applicable for liquids .	
<b>Flammability Limit in Air</b>		
<b>Upper flammability or explosive limits</b>	No data available	
<b>Lower flammability or explosive limits</b>	No data available	
<b>Vapor pressure</b>	No data available	
<b>Relative vapor density</b>	No data available	
<b>Relative density</b>	0.83	

# SAFETY DATA SHEET

ANCHORWELD 6031 PANEL ADHESIVE  
Revision Number 2.03

Revision date 09-Aug-2022  
Supersedes Date: 07-Jul-2022

Water solubility	Insoluble in water
Solubility(ies)	No data available
Partition coefficient	No data available
Autoignition temperature	536 °C
Decomposition temperature	No data available
Kinematic viscosity	No data available
Dynamic viscosity	No data available
Explosive properties	No information available
Oxidizing properties	No information available
<b>Other information</b>	
Solid content (%)	No information available
Liquid Density	No information available
VOC content	No information available

## Section 10: Stability and reactivity

### Reactivity

Reactivity No information available.

### Chemical stability

Stability Stable under normal conditions.

### Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

### Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

### Conditions to avoid

Conditions to avoid Heat, flames and sparks.

### Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

### Hazardous decomposition products

Hazardous decomposition products None known based on information supplied.

## Section 11: Toxicological information

### Acute toxicity

### Information on likely routes of exposure

#### Product Information

**Inhalation** Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

**Eye contact** Specific test data for the substance or mixture is not available. May cause irritation. Causes serious eye irritation. (based on components). May cause redness, itching, and

# SAFETY DATA SHEET

ANCHORWELD 6031 PANEL ADHESIVE  
Revision Number 2.03

Revision date 09-Aug-2022  
Supersedes Date: 07-Jul-2022

pain.

## Skin contact

Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).

## Ingestion

Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

## Symptoms

Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

## Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg  
ATEmix (inhalation-vapor) 10,316.728

## Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Naphtha, petroleum, hydrotreated light, <0.1% Benzene	>5000 mg/kg (Rattus)	> 3160 mg/kg (Oryctolagus cuniculus)	=73680 ppm (Rattus) 4 h
Acetone	=5800 mg/kg (Rattus) 3000 mg/Kg (mouse)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Toluene	=5580 mg/kg (Rattus)	= 12000 mg/kg (Oryctolagus cuniculus)	>20 mg/L (Rattus) 4 h
Pentane	>2000 mg/kg (Rattus)	= 3000 mg/kg (Oryctolagus cuniculus)	=364 g/m <sup>3</sup> (Rattus) 4 h
Hexane	=25 g/kg (Rattus)	= 3000 mg/kg (Oryctolagus cuniculus)	=48000 ppm (Rattus) 4 h
Zinc oxide	>5000 mg/kg (Rattus)	LD50 >2000 mg/Kg (Rattus) (OECD 402)	LC50 (4h) >5.7 mg/l
Rosin	>2000 mg/Kg (Rattus)	> 2500 mg/kg (Oryctolagus cuniculus)	=1.5 mg/L (Rattus) 4 h

See section 16 for terms and abbreviations

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

### Skin corrosion/irritation

Classification based on data available for ingredients. Causes skin irritation. May cause skin irritation.

Component Information					
Toluene (108-88-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No. 440/2008, Annex, B.4	Rabbit	Dermal			Irritant

Hexane (110-54-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal		24 hours	irritant

**Serious eye damage/eye irritation** Classification based on data available for ingredients. Causes serious eye irritation.



# SAFETY DATA SHEET

ANCHORWELD 6031 PANEL ADHESIVE  
Revision Number 2.03

Revision date 09-Aug-2022  
Supersedes Date: 07-Jul-2022

**Respiratory or skin sensitization** No information available.

Component Information			
Acetone (67-64-1)			
Toluene (108-88-3)			
Method	Species	Exposure route	Results
Regulation (EC) No. 440/2008, Annex, B.6 (Maximization test)	Guinea pig		No sensitization responses were observed

**Germ cell mutagenicity** No information available.

Component Information		
Toluene (108-88-3)		
Method	Species	Results
Regulation (EC) No. 440/2008, Annex, B.13/14 (Ames test)	Salmonella typhimurium	Not mutagenic
OECD Test No. 476: In vitro Mammalian Cell Gene Mutation Test	Mouse	Not mutagenic

## Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	Australia	European Union	IARC
Naphtha, petroleum, hydrotreated light, <0.1% Benzene 64742-49-0	Carc. 1A		
Toluene 108-88-3			Group 3

Legend

**IARC (International Agency for Research on Cancer)**

Group 3 - Not Classifiable as to Carcinogenicity in Humans

**Reproductive toxicity** Contains a known or suspected reproductive toxin. Classification based on data available for ingredients. Suspected of damaging fertility or the unborn child.

Component Information		
Toluene (108-88-3)		
Method	Species	Results
OECD 407	in vivo	Reproductive toxicant

**STOT - single exposure** May cause drowsiness or dizziness. May cause respiratory irritation.

**STOT - repeated exposure** May cause damage to organs through prolonged or repeated exposure.

Component Information					
Toluene (108-88-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No. 440/2008, Annex, B.26	Rat, male, female	Oral		91 days	NOAEL: 625 mg/kg
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat, male, female	Inhalation, vapor			NOAEL: 1.131 mg/l

# SAFETY DATA SHEET

ANCHORWELD 6031 PANEL ADHESIVE  
Revision Number 2.03

Revision date 09-Aug-2022  
Supersedes Date: 07-Jul-2022

**Aspiration hazard** May be fatal if swallowed and enters airways.

## Section 12: Ecological information

### Ecotoxicity

#### Aquatic ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Naphtha, petroleum, hydrotreated light, <0.1% Benzene 64742-49-0	-	LC50: =8.41mg/L (96h, Oncorhynchus mykiss)	-	LC50: =2.6mg/L (96h, Chaetogammarus marinus)
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss )	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)
Toluene 108-88-3	EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 19.7 mg/L 30 min	EC50: =11.5mg/L (48h, Daphnia magna) EC50: 5.46 - 9.83mg/L (48h, Daphnia magna)
Pentane 109-66-0	-	LC50: =11.59mg/L (96h, Pimephales promelas) LC50: =9.87mg/L (96h, Oncorhynchus mykiss) LC50: =9.99mg/L (96h, Lepomis macrochirus)	-	EC50: =9.74mg/L (48h, Daphnia magna)
Hexane 110-54-3	-	LC50: 2.1 - 2.98mg/L (96h, Pimephales promelas)	-	EC50: >1000mg/L (24h, Daphnia magna)
Zinc oxide 1314-13-2	LC 50 (72Hr) 0.136 mg/L	LC50 (96h) =0.7 mg/L (Danio rerio)	-	LC 50 (48Hr) =0.5 mg/l (Ceriodaphnia dubia)
Rosin 8050-09-7	EC50: =400mg/L (72h, Desmodemus subspicatus)	LC50 (96h) >10mg/L (Danio rerio)	EC50 = 31.5 mg/L 30 min	EC50 48 h >100 mg/L (Daphnia magna )

### Persistence and degradability

**Persistence and degradability** No information available.

#### Component Information

##### Acetone (67-64-1)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	biodegradation	91 % Readily biodegradable

##### Zinc oxide (1314-13-2)

Method	Exposure time	Value	Results
			The methods for determining biodegradability are not applicable to inorganic substances

### Bioaccumulative potential

# SAFETY DATA SHEET

ANCHORWELD 6031 PANEL ADHESIVE  
Revision Number 2.03

Revision date 09-Aug-2022  
Supersedes Date: 07-Jul-2022

**Bioaccumulation** There is no data for this product.

## Component Information

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Toluene 108-88-3	3.93
Pentane 109-66-0	3.45
Hexane 110-54-3	4
Rosin 8050-09-7	7.7

## Mobility

**Mobility in soil** No information available.

**Mobility** No information available.

## Other adverse effects

**Other adverse effects** No information available.

## Section 13: Disposal considerations

### Disposal methods

**Waste from residues/unused products** Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

## Section 14: Transport information

### ADG

**UN number or ID number** UN1133  
**UN proper shipping name** Adhesives  
**Transport hazard class(es)** 3  
**Packing group** II  
**Special Provisions** \*  
**Limited quantity (LQ)** 5 L  
**Description** UN1133, Adhesives, 3, II

**Hazchem code** •3YE

### IATA

**UN number or ID number** UN1133  
**Transport hazard class(es)** 3  
**Packing group** II  
**ERG Code** 3L  
**Special Provisions** A3  
**Limited quantity (LQ)** 1 L  
**Description** UN1133, Adhesives, 3, II

### IMDG

**UN number or ID number** UN1133  
**Transport hazard class(es)** 3

# SAFETY DATA SHEET

ANCHORWELD 6031 PANEL ADHESIVE  
Revision Number 2.03

Revision date 09-Aug-2022  
Supersedes Date: 07-Jul-2022

Packing group II  
EmS-No F-E, S-D  
Limited Quantity (LQ) 5 L  
Marine pollutant NP  
Description UN1133, Adhesives, 3, II, (-10°C c.c.)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code  
No information available

## Section 15: Regulatory information

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National regulations

##### Australia

See section 8 for national exposure control parameters

##### Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number 5

#### Major hazard (accident/incident planning) regulation

Verify that license requirements are met

#### Hazardous chemical

Liquids that meet the criteria for Class 3 Packing Group II or III  
Liquids with flash points <61°C kept above their boiling points  
at ambient conditions

#### Threshold quantity (T)

50 000  
200

#### National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Acetone 67-64-1	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Toluene 108-88-3	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Pentane 109-66-0	20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Hexane 110-54-3	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total

# SAFETY DATA SHEET

ANCHORWELD 6031 PANEL ADHESIVE  
Revision Number 2.03

Revision date 09-Aug-2022  
Supersedes Date: 07-Jul-2022

	400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Zinc oxide 1314-13-2	10 tonne/yr Threshold category 1

## International Inventories

<b>AIIC</b>	Listed
<b>NZIoC</b>	Not Listed
<b>ENCS</b>	Not Listed
<b>IECSC</b>	Not Listed
<b>KECL</b>	Not Listed
<b>PICCS</b>	Not Listed

## Legend:

- AIIC** - Australian Inventory of Industrial Chemicals
- NZIoC** - New Zealand Inventory of Chemicals
- ENCS** - Japan Existing and New Chemical Substances
- IECSC** - China Inventory of Existing Chemical Substances
- KECL** - Korean Existing and Evaluated Chemical Substances
- PICCS** - Philippines Inventory of Chemicals and Chemical Substances

## International Regulations

**The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable

**The Stockholm Convention on Persistent Organic Pollutants** Not applicable

**The Rotterdam Convention** Not applicable

## Europe

### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

#### **SVHC: Substances of Very High Concern for Authorization:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### **2015/863/EU - RoHS**

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

### **Section 16: Any other relevant information**

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 09-Aug-2022

#### **Revision Note**

SDS sections updated: 3.

#### **Key or legend to abbreviations and acronyms used in the safety data sheet**

#### **Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

#### **Section 11: TOXICOLOGICAL INFORMATION**

# SAFETY DATA SHEET

ANCHORWELD 6031 PANEL ADHESIVE  
Revision Number 2.03

Revision date 09-Aug-2022  
Supersedes Date: 07-Jul-2022

---

LD50 (lethal dose)

**Section 12: Ecological information**

EC50 (effective concentration)

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**