



Technical Data Sheet

U-WALL (PATENT PENDING) Spacer at a wall edge

COMPONENTS

The U-WALL is composed of 1 piece.

CHARACTERISTICS

Weight: **0,039 kg**

Additional height: **3 mm**

To be used only with 6mm tabs (maximum).

MATERIAL

Copolymer polypropylene (CPP)

Composition: +/- **80%** first grade pre-selected recycled PPC, and +/- **20%** Talc + Masterbatch black

Designed and manufactured in Europe

Use of recycled materials exclusively of EU origin

Resistant to weathering, sea salts, algae and a wide range of chemicals

Temperature range: **-30 °C to +80 °C**

PACKAGING

Pieces per carton: **24 pcs**

Carton weight: **1,03 kg**

Carton dimension: **220 x 220 x 65 mm**

Cartons per pallet: **620 pcs**

Pieces per pallet: **14880 pcs**

Pallet dimensions: **100x120x220 cm**



APPLICATIONS

Maintains a regular space (5 mm) between the paver and the wall.

Accessories are available for applications with various outdoor finishes, such as granite stone pavers, composite / timber decking, ceramic tiles and fibreglass or metal.

SAFETY INSTRUCTIONS

Buzon pedestals and accessories are designed to support external raised floors for pedestrian traffic only and are not designed to support or be subjected to moving and/or vibrating machinery & equipment, including maintenance, cleaning vehicles, automobiles and other similar equipment.



043-055-1351
Made From Min. 50%
Recycled Content



With the support
of



Wallonie